

Jaws	POWER PACK AND JAW SELECTION CHART								
	MSP-1	SP-01P	SP-02P	SP-002	SP-003	SP-004	SP-005	SP-006	SP-008
PGC-1CH Flush Cut	Soft Plastic Gates 0.093" max 2.36 mm max								
PGC-2 Flush Cut - 18 °		Soft Plastic Gates 0.125" max 3.17 mm max	Soft Plastic Gates 0.187" max 4.75 mm max						
PGC-2-45 Flush Cut - 45 °		Soft Plastic Gates 0.125" max 3.17 mm max	Soft Plastic Gates 0.187" max 4.75 mm max						
PGC-2-60 Flush Cut - 60 °		Soft Plastic Gates 0.125" max 3.17 mm max	Soft Plastic Gates 0.187" max 4.75 mm max						
PGC-2-90 Flush Cut - 90 °		Soft Plastic Gates 0.125" max 3.17 mm max	Soft Plastic Gates 0.187" max 4.75 mm max						
PGC-7 Flush Cut - Straight		Soft Plastic Gates 0.125" max 3.17 mm max	Plastics Gates Only 0.187" max 4.75 mm max						
PGC-8 Flush Cut - End Cutter		Soft Plastic Gates 0.125" max 3.17 mm max	Soft Plastic Gates 0.187" max 4.75 mm max						
PGC-4 Flush Cut - 25 °				Soft Plastic Gates 0.187" max 4.75 mm max	Soft Plastic Gates 0.218" max 5.54 mm max	Soft Plastic Gates 0.28" max 6.35 mm max	Soft Plastic Gates 0.375" max 9.53 mm max	Soft Plastic Gates 0.375" max 9.53 mm max	Soft Plastic Gates 0.375" max 12.7 mm max
PGC-4-30 Flush Cut - 30 °				Soft Plastic Gates 0.187" max 4.75 mm max	Soft Plastic Gates 0.218" max 5.54 mm max	Soft Plastic Gates 0.28" max 6.35 mm max	Soft Plastic Gates 0.375" max 9.53 mm max	Soft Plastic Gates 0.375" max 9.53 mm max	Soft Plastic Gates 0.375" max 12.7 mm max
PGC-4-45 Flush Cut - 45 °				Soft Plastic Gates 0.187" max 4.75 mm max	Soft Plastic Gates 0.218" max 5.54 mm max	Soft Plastic Gates 0.28" max 6.35 mm max	Soft Plastic Gates 0.375" max 9.53 mm max	Soft Plastic Gates 0.375" max 9.53 mm max	Soft Plastic Gates 0.375" max 12.7 mm max
PGC-4-60 Flush Cut - 60 °				Soft Plastic Gates 0.187" max 4.75 mm max	Soft Plastic Gates 0.218" max 5.54 mm max	Soft Plastic Gates 0.28" max 6.35 mm max	Soft Plastic Gates 0.375" max 9.53 mm max	Soft Plastic Gates 0.375" max 9.53 mm max	Soft Plastic Gates 0.375" max 12.7 mm max
PGC-4-90 Flush Cut - 90 °				Soft Plastic Gates 0.187" max 4.75 mm max	Soft Plastic Gates 0.218" max 5.54 mm max	Soft Plastic Gates 0.28" max 6.35 mm max	Soft Plastic Gates 0.375" max 9.53 mm max	Soft Plastic Gates 0.375" max 9.53 mm max	Soft Plastic Gates 0.375" max 12.7 mm max
MCD-1 Semi-Flush Rise - 15 °	Soft Copper/Metal 0.032" max 0.81 mm max								
MCD-2 Semi-Flush Rise - 35 °	Soft Copper/Metal 0.032" max 0.81 mm max								
MFS-1 Shear Action Cut	Soft Copper/Metal 0.047" max 1.94 mm max								
MSJ-1 Unhardened Jaws	Blank Jaws								
SJ-1A Unhardened Jaws		Blank Jaws	Blank Jaws						
CD-1 Semi-Flush Cut - 45 °		Copper/Soft Metal 0.093" max 2.36 mm max	Copper/Soft Metal 0.125" max 3.17 mm max						
CD-3 Semi-Flush Cut - 15 °		Copper/Soft Metal 0.093" max 2.36 mm max	Copper/Soft Metal 0.093" max 2.36 mm max						
CD-4CH Semi-Flush, Center Cut		Copper/Soft Metal 0.093" max 2.36 mm max	Copper/Soft Metal 0.093" max 2.36 mm max						
CD-6 Flush Cut - 15 °		Plastics Only 0.125" max 3.17 mm max	Plastics Only 0.187" max 4.75 mm max						
FS-1/FS1CH Shear Action Cut		fine wires, nickel Ribbon or Soft Wire 0.093" max 2.36 mm max	fine wires, nickel Ribbon or Soft Wire 0.125" max 3.17 mm max						
PC-311F Flush Cut - 25 °		PC Boards 0.28" opening max 6.60 mm	PC Boards 0.28" opening max 6.60 mm						
B-31 Straight Cut - Side				Copper/Soft Wire 0.093" max 2.36 mm max	Copper/Soft Wire 0.125" max 3.17 mm max	Copper/Soft Wire 0.156" max 3.96 mm max	Copper/Soft Wire 0.187" max 4.75 mm max	Copper/Soft Wire 0.187" max 4.75 mm max	Copper/Soft Wire 0.25" max 6.35 mm max
B-32 Straight Cut - Side				Copper/Soft Wire 0.093" max 2.36 mm max	Copper/Soft Wire 0.125" max 3.17 mm max	Copper/Soft Wire 0.156" max 3.96 mm max	Copper/Soft Wire 0.187" max 4.75 mm max	Copper/Soft Wire 0.187" max 4.75 mm max	Copper/Soft Wire 0.25" max 6.35 mm max
B-33 Straight Cut - Center				Copper/Soft Wire 0.093" max 2.36 mm max	Copper/Soft Wire 0.125" max 3.17 mm max	Copper/Soft Wire 0.156" max 3.96 mm max	Copper/Soft Wire 0.187" max 4.75 mm max	Copper/Soft Wire 0.187" max 4.75 mm max	Copper/Soft Wire 0.25" max 6.35 mm max
B-35 Straight Cut - Center				Copper/Soft Wire 0.093" max 2.36 mm max	Copper/Soft Wire 0.125" max 3.17 mm max	Copper/Soft Wire 0.156" max 3.96 mm max	Copper/Soft Wire 0.187" max 4.75 mm max	Copper/Soft Wire 0.228" max 5.79 mm max	Copper/Soft Wire 0.25" max 5.79 mm max
B-38 Straight Cut - Side				Stainless Steel Braid 0.093" max 2.36 mm max	Stainless Steel Braid 0.125" max 3.17 mm max	Stainless Steel Braid 0.156" max 3.96 mm max	Stainless Steel Braid 0.187" max 4.75 mm max	Stainless Steel Braid 0.25" max 6.35 mm max	Stainless Steel Braid 0.25" max 6.35 mm max
D-31 Diagonal Cut - 45 °				Copper/Soft Wire 0.093" max 2.36 mm max	Copper/Soft Wire 0.125" max 3.17 mm max	Copper/Soft Wire 0.156" max 3.96 mm max	Copper/Soft Wire 0.187" max 4.75 mm max	Copper/Soft Wire 0.25" max 6.35 mm max	Copper/Soft Wire 0.25" max 6.35 mm max
D-33 Diagonal Cut - 25 °				Copper/Soft Wire 0.093" max 2.36 mm max	Copper/Soft Wire 0.125" max 3.17 mm max				
D-4 Diagonal Cut - 25 °				Copper/Soft Wire 0.093" max 2.36 mm max	Copper/Soft Wire 0.125" max 3.17 mm max	Copper/Soft Wire 0.156" max 3.96 mm max	Copper/Soft Wire 0.187" max 4.75 mm max	Copper/Soft Wire 0.218" max 5.54 mm max	Copper/Soft Wire 0.218" max 5.54 mm max
E-3 Blade and Anvil				Electrical Cable/Soft Wire 0.125" max 4.75 mm max	Electrical Cable/Soft Wire 0.187" max 4.75 mm max	Electrical Cable/Soft Wire 0.25" max 6.35 mm max	Electrical Cable/Soft Wire 0.312" max 7.92 mm max	Electrical Cable/Soft Wire 0.312" max 7.92 mm max	Electrical Cable/Soft Wire 0.375" max 9.52 mm max
E-4 Blade and Anvil				Electrical Cable/Soft Wire 0.125" max 4.75 mm max	Electrical Cable/Soft Wire 0.187" max 4.75 mm max	Electrical Cable/Soft Wire 0.25" max 6.35 mm max	Electrical Cable/Soft Wire 0.312" max 7.92 mm max	Electrical Cable/Soft Wire 0.312" max 7.92 mm max	Electrical Cable/Soft Wire 0.375" max 12.7 mm max
SA-2000 Shear Cut - Cable				Copper Cable 0.187" max 4.75 mm max	Copper Cable 0.25" max 6.35 mm max	Copper Cable 0.312" max 7.92 mm max	Copper Cable 0.375" max 9.53 mm max	Copper Cable 0.375" max 9.53 mm max	Copper Cable 0.5" max 12.7 mm max
A-3 Unhardened Jaw				Blank Jaws	Blank Jaws	Blank Jaws	Blank Jaws	Blank Jaws	Blank Jaws

